

# 雷射刻號機 (Laser Marker)

## 標準製程

只有 6INCH-3(大字)和 6INCH-2(小字)刻號檔案可以使用，其餘檔案

皆為機台驗機測試所使用。

|                      |                                   |               |
|----------------------|-----------------------------------|---------------|
| Character Input Mode | [1 : Standard 2 : Special]        | : 1           |
| Marking Mode         | [1 : Straight 2 : Circular]       | : 1           |
| Character type       | [1 : SEMI 2 : OCR-8 3 : DOT]      | : 1           |
| Dot type             | [1 : 5*9 2 : 9*17 3 : 10*18]      | :             |
| Marking level        | [0-10]                            | :             |
| Character Direction  | [1 : Erect 2 : Upside-down]       | : 1           |
| Wafer Size           | [3-8]                             | : 6 [inch]    |
| Alignment            | [1 : O.F 2 : Notch]               | : 1           |
| Character size       | [1-10]                            | : 2.5X        |
| Character Space      |                                   | : 1.8 [mm]    |
| OF Rotation Angle    | [0-360]                           | : 0°          |
| Laser Pulse Rate     | [0.1-10]                          | : 1.0 [kHz]   |
| Marking speed        | [1-200]                           | : 10 [mm/sec] |
| Marking start point  | X : 10.0 [mm] Y : 27.0 [mm]       |               |
| Centering            | [1 : Twice 2 : once]              | : 2           |
| Checksum             | [1 : No 2 : Yes(Stick -) 3 : Yes] | : 1           |
| Laser power          | [0-100]                           | : 100 [%]     |